

Marine Boiler Specifications					
Model	MC800	MC1200	MC1500	MC2500	MC4000
Overall Height	4'8"	4'6"	5'10"	6'6"	7'
Overall Width	3'6"	3'6"	4'	4'8"	5'3"
Overall Length	6'	6'	6'6"	8'	8'6"
Dry Weight, Lbs.	2,200	3,500	5,600	7,500	11,700
Wet Weight, Lbs.	2,900	4,400	8,100	10,000	15,300
*Lbs. of Steam Per Hr. Normal	800	1,200	1,500	2,500	4,000
*Lbs of Steam Per Hr. Max.	800	1,440	1,800	3,000	4,800
Pressure, PSIG	100, 125 150, and 200 On All M				
Fuel	Diesel On All Models				
Ignition	10,000 Volt Direct Ignition			Oil P	
Burner Operation	On-Off	Modulating Through W			
Draft	Forced On All Models				
Burner Nozzle, Cap.	Fixed	Variable			
* From and at 100 Degree Water at 100 PSI					

MC5000	MC7500	MC9000
7'10"	8'7"	8'7"
6'	6'5"	6'5"
8'6"	12'5"	12'5"
12,500	18,000	18,000
16,400	24,500	24,500
5,000	7,500	9,000
6,000	7,500	9,000
odels		
ilot Direct Ignition		
ide Range		